

BEAMS DIMENSION AND PROPERTIES

Designation	DEPTH OF SECTION(MM) (A)	WIDTH OF FLANGE (MM) (B)	THICKNESS OF WEB(MM) (C)	THICKNESS OF FLANGE(MM) (D)	WEIGHT / MTR (KG)
ISMB 100	100	50	4.7	7.0	8.09
ISMB 125	125	70	5.0	8.0	13.02
ISMB 150	150	75	5.0	8.0	15.00
ISMB 175	175	85	5.8	9.0	19.05
ISMB 200	200	100	5.7	10.0	24.02
ISMB 250	250	125	6.9	12.5	37.03
ISMB 300	300	140	7.7	13.1	46.00
ISMB 350	350	140	8.1	14.2	52.04
ISMB 400	400	140	8.9	16.0	61.05
ISMB 450	450	150	9.4	17.2	72.04
ISMB 500	500	180	10.2	17.4	86.09
ISMB 600	600	210	12.0	20.3	123.00
RSJ 116X100	116	100	8.0	10.3	23.00
HB 152X152	152	152	7.9	11.9	37.00
HB 152X152	152	152			34.00
HB 152X152	152	152			31.00
HB 200X 152	200	152	8.9	16.5	52.00
HB 200X200	200	200	7.8	9.0	40.00